

Link do produktu: <https://www.diablosat.pl/antena-plaska-selfsat-h50m4-quad-2x-sat-80cm-p-4043.html>



ANTENA PŁASKA SELFSAT - H50M4 QUAD 2X SAT (= 80CM)

Cena	1 299,00 zł
Cena poprzednia	1 349,00 zł
Czas wysyłki	4 dni
Numer katalogowy	SELSAT - H50M4 QUAD 2X SAT (= 80CM)
Kod producenta	SELSAT - H50M4 QUAD 2X SAT (= 80CM)
Producent	Selfsat

Opis produktu



SELSAT-H50M



SELSAT

- 1-sza wielo-odbiorcza płaska antena satelitarna na świecie
- Odbieranie dwóch satelit w tej samej chwili
(Astra1 & Hotbird / Astra4A & Thor / Astra3 & Astra1)
- Automatyczna zmiana satelity poprzez DiSEqC
- Praca w pełnym zakresie pasma Ku
- Wyjście : Single / Twin / Quad
- Wsporniki do montażu



SELSAT



- Antena H50M składa się z dwóch anten H30D
- Specjalnie skrócone kąty do odbioru dwóch satelitów
- Wsporniki do przeszukiwania satelity

SELSAT



1

H50M

1st Astra1 19.2E
2nd Hotbird 13.0E

2

H50M

1st Astra4A 4.9E
2nd Thor 0.8W

3

H50MN (Optional)

1st Astra3 23.5E
2nd Astra1 19.2E

- Set-up pierwszą satelitę jako standard (nie ma potrzeby, aby konfigurować 2-gą satelitę osobno).

- Zmiana satelity za pomocą DiSEqC

- Włączony multi- odbiór

SELSAT



H50M

Astra 1 - 19.2E
Hotbird - 13.0E



H50M

Astra 4A - 4.9E
Thor - 0.8W



H50MN (Optional)

Astra 3 - 23.5E
Astra 1 - 19.2E

Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	33.7dBi @ 12.7GHz
Size(W×D×H)	527 × 520 × 112mm
Weight	8.5 kg
Current Consumption	150mA (max)
Target Satellite	ASTRA1 & HOTBIRD / ASTRA4A & THOR
Switching Satellite	DiSEqC
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB Output	1 / 2 / 4 output
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
LNB Noise Figure at 25°C	0.2 dB Typical
Input VSWR	2.5 : 1 Typical
Output VSWR	2.5 : 1 Typical
Conversion Gain	60 dB Typical
Gain Flatness	6dB p-p (max)
Power Supply	12~14V DC (Vertical) / 16~19V DC (Horizontal)

Wysokiej jakości płaska antena satelitarna marki **SELSAT model H50M**. Antenę stosujemy w miejscach gdzie nie można zainstalować standardowej anteny satelitarnej.

Zaletą anteny jest łatwa instalacja, dobra jakość sygnału, może być zamontowana praktycznie wszędzie. Antena jest mała gabarytowo więc można ją zabrać w podróż lub na camping. Jedyna antena z tej serii, która odbiera sygnał z dwóch satelitów w jednym momencie. Niestety nie ma możliwości instalacji we wnętrzu budynku lub apartamentu czy też za szklaną szybą.

H30D:

- zysk anteny - 33,7 dBi
- antena w trzech wersjach LNB: Single, Twin, Quad
- wymiary 517 x 277 x 58 mm
- waga 4,5 kg

H21D+:

- zysk anteny - 34,5 dBi
- antena w trzech wersjach LNB: Single, Twin, Quad
- jedyna antena z tej serii z wymiennym LNB
- wymiary 566 x 300 x 67 mm
- waga 7 kg

H50D:

- zysk anteny - 36,1 dBi
- antena w trzech wersjach LNB: Single, Twin, Quad
- wymiary 517 x 514 x 58 mm
- waga 8,5 kg

H50M:

- zysk anteny - 33,7 dBi

- antena w trzech wersjach LNB: Single, Twin, Quad
- jedyna antena z tej serii, która wyłapuje sygnał z dwóch satelit na raz
 - zmiana oglądanej satelity poprzez DiSEqC
 - wymiary 527 x 520 x 112 mm
 - waga 8,5 kg

Poniżej porównanie anten z naszej oferty:

H30D

MODEL	SELSAT-H30D / SELSAT-H30D2 / SELSAT-H30D4
Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	33.7 dBi @ 12.7 GHz
Size(WxDxH)	517x277x58mm
Weight	4.5kg
Current Consumption	150mA (max)
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB output	1 output / 2 output / 4 output
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
Conversion Gain	60 dB Typical
Gain flatness	6dB p-p (max)
Power supply	12~14V DC (Vertical) / 16~19V DC (Horizontal)

H21D+

Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	34.5dBi @ 12.7GHz
Size(WxDxH)	566 x 300 x 67mm
Weight	7.0kg
Current Consumption	150mA (max)
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB output	LNB Interchangeable (Single/ Twin / Quad)
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
LNB Noise Figure at 25°C	0.2 dB Typical
Input VSWR	2.5 : 1 Typical
Output VSWR	2.5 : 1 Typical
Conversion Gain	60 dB Typical
Gain flatness	6dB p-p (max)
Power supply	12~14V DC (Vertical) 16~19V DC (Horizontal)

H50D

Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	36.1dBi @ 12.7GHz
Size(WxDxH)	517 x 514 x 58mm
Weight	8.5kg
Current Consumption	150mA (max)
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB output	1/2/4 output
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
LNB Noise Figure at 25°C	0.2 dB Typical
Input VSWR	2.5 : 1 Typical
Output VSWR	2.5 : 1 Typical
Conversion Gain	60 dB Typical
Gain flatness	6dB p-p (max)
Power supply	12~14V DC (Vertical) 16~19V DC (Horizontal)

H50M

Input Satellite Frequency	10.7~12.75GHz
Polarization	Vertical & Horizontal
Antenna Gain	33.7dBi @ 12.7GHz
Size(WxDxH)	527 x 520 x 112mm
Weight	8.5 kg
Current Consumption	150mA (max)
Target Satellite	Astra3 & Astra1
Switching Satellite	DiSEqC
Operating Temperature	-30°C to +60°C
Storage Temperature	-40°C to +80°C
LNB Output	1/2/4 output
Changeover Low / High	0KHz / 22KHz
LNB Output Frequency	950~1,950MHz / 1,100~2,150MHz
L.O. Frequency	9.75GHz / 10.6GHz
LNB Noise Figure at 25°C	0.2 dB Typical
Input VSWR	2.5 : 1 Typical
Output VSWR	2.5 : 1 Typical
Conversion Gain	60 dB Typical
Gain Flatness	6dB p-p (max)
Power Supply	12~14V DC (Vertical) / 16~19V DC (Horizontal)

CECHY PRODUKTU

Zysk anteny dBi

33,7

Max ilość podłączonych tunerów	4
Dodatkowe cechy	2 x SAT

**W razie jakichkolwiek pytań
pisz na adres admin@cardsplitter.pl
lub dzwoń pod numer **531-666-888****